

## Dixie Speedway Demo Derby Rules 2024

\*ONLY SMALL CARS ALLOWED. NO MIDSIZE, TRUCKS, OR LARGE CARS

ALL CARS MUST PARTICIPATE IN COMPETITION INDIVIDUALLY. NO TEAMS.

- A. Any V-6 or 4 cyl FWD car.
- B. Cars must be stripped of all chrome, interior and glass.
- C. Windshield bars with a wire mesh are highly recommended.
- D. Helmets and eye protection must be worn at all times. Seatbelts must be operable in use.
- E. Cars must remain stock unless otherwise noted.
- F. You may weld doors solid with 4- inch wide  $\frac{1}{2}$ - thick strips.
- G. Driver's door may have a piece of flat steel 6- inches wide  $\frac{3}{4}$  - inch thick overlapping the seams by 6 - inches, 3- inches on each side of the seam.
- H. You may have a 4-point cage, max. 4-inches in diameter or something similar. Must be welded or bolted to the floorboard to protect the driver.
- I. Hoods must be wired or bolted in 4-places, max.  $\frac{1}{2}$  inch bolts, bolt or wire sheet metal to sheet metal. (No welds)
- J. A 4" x 4" hole must be cut in the hood, over the area of the carburetor in case of an engine fire, this will help the fire officials.
- K. Trunk lids may be welding shut but must have an inspection hole.
- L. Electric fuel pumps must have a shut off switch within reach from the outside and in the driver's area of the car, and clearly marked ON / OFF.
- M. Max. of 5 gallons of gas in the tank.
- N. Battery may be relocated in a safe place and securely fastened with a cover on the passenger's side of the car.
- O. No steel studded tires, Mud grips or wheel weights allowed, No Double tires.
- P. Valve stem protector's OK. (Must meet judges safety standards or be taken off.)
- Q. Bumpers and brackets may be fully welded on so we don't have a bunch of loose bumpers on the track. Bumper shocks can be collapsed and welded.
- R. No welding of body seams.
- S. No reinforcing the body with extra plates of steel.
- T. No double skinning of sheet metal.
- U. No patching of rust on the entire car.